




Description	Part no. Article no.	Price see price list	Std. pack	Notes
Gateway				
PROFIBUS-DP				
 <p>Gateway with integrated supply for the SmartWire module and control voltage for the switchgear. Connection to PROFIBUS-DP as slave Transmission rate: 9.6 kBit/s to 12 MBit/s 9 pole SUB-D socket Address range: 1 – 126 - Connection to SmartWire module as Master. - supports 16 SmartWire modules.</p>	SWIRE-GW-DP 107027		1 off	Other Gateways easy-NET/CANopen Page → page 4/44
Modules				
 <p>SmartWire module to assemble on the contactors DILM7...DILM32. - One module is necessary per contactor. - Connection to SmartWire- Gateway as Slave. - Max. 16 SmartWire modules per chain. - 1 digital input for potential-free contact. - Signalling contactor switch position.</p>	SWIRE-DIL 107028		1 off	<ul style="list-style-type: none"> • Take account of the max. current consumption of the contactor coils per SmartWire chain. • Length of connection cable at the input and the electrical interlock < 2.8 m. • A2 terminal of the contactor must not be bridged. • Electrical interlocking only possible via the terminals on the module for DILM. • Wiring kits DILM 12-XRL and PKZM0-XRM12 cannot be used. • Connection terminals for electrical interlocking are not suitable for safety technology.
 <p>Power module for supplying the control voltage. - Connection on SmartWire Gateway as interactive station (no address).</p>	SWIRE-PF 107029		1 off	Max. 4 power modules per SmartWire chain.
Accessories				
SmartWire connection cable				
Length: 85 mm	SWIRE-CAB-008 107032		25 off	Cable lengths: Engineering → Engineering SmartWire connection system
Length: 110 mm	SWIRE-CAB-011 107033		25 off	
Length: 150 mm	SWIRE-CAB-015 107034		5 off	
Length: 250 mm	SWIRE-CAB-025 107035		5 off	
Length: 1000 mm	SWIRE-CAB-100 107036		1 off	
Length: 2000 mm	SWIRE-CAB-200 107037		1 off	
Termination plug				
Termination plug for last SmartWire module, 6 pole, no electrical function.	SWIRE-CAB-000 107031		25 off	
Data cable				
6 core, flat-band cable, length: 100 m.	SWIRE-CAB-100M 107038		1 off	Pre-manufacture of cable only possible with special tool.
Plug				
6 plug for flat-band cable.	SWIRE-CAB-CON 107039		50 off	
NHI-E with cable				
NHI-E-10-PKZO with connection cable AWG18 blue, for connection to SmartWire module for DILM.	NHI-E-10L-PKZO 107040		5 off	

